

RUPEDL P-6541 UHPD 5W-40 CK-4

Description

RUPEDL P-6541 UHPD 5W-40 CK-4 with the latest ultra-pro additive system is an premium heavy duty engine oil which meet the requirements of PC-11 engine oil test as well as the diesel engines where API CK-4 and below is required.

RUPEDL P-6541 UHPD 5W-40 CK-4 adapts the latest additive technology which provided excellent anti-oxidation performance, extending useful life of the oil.

Applications

RUPEDL P-6541 UHPD 5W-40 CK-4 is a mixed fleet motor oil recommended for both naturally aspirated and turbo-charged four stroke diesel engines and for stroke gasoline engines in which API CK-4 or API SN service category requirement. This product is excellent for use in new advance engines which fitted with DPF with DFI (Direct Fuel Inject) common rail system. As well as the EGR or SCR after treatment device engines.

Specifications/Recommendations

API SN/CK-4/CJ-4 ACEA E9-08/E7-08
Caterpillar ECF-3 Cummins CES 20081
VOLVO VDS-4 JASO DH-2

MB 228.3/228.31/235.27 MTU Type 1 & 2 MAN 3575











Rupedl P-6541 UHPD 5W-40 CK-4	Typical Spec.	Typical Result
Density at 15℃	Report	0.8563
Kinematic Viscosity at 100°C, cSt	12.5-16.3	14.59
Kinematic Viscosity at 40 °C, cSt	Report	93.26
Viscosity Index	Min. 160	170
Flash Point (Open) °C	Min. 200	233
Color	Report	3.0
TBN, mg/KOH/g	Min. 9.5	10.0
Pour Point, °C	Max21	-45
Sulfur Ash %	Max. 1.0	1.0
CCS-25℃	Max. 7000	6152

*We reserve the right to alter the general characteristics of our products in order to let our consumers benefit from the latest technical development.

















































































